

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(1) International Patent Classification 5 :

H04N 5/91

A1

(11) International Publication Number:

WO 91/16791

(43) International Publication Date:

31 October 1991 (31.10.91)

(21) International Application Number: PCT/EP91/00738

(22) International Filing Date: 18 April 1991 (18.04.91)

(30) Priority data:

9000951

20 April 1990 (20.04.90)

NL

(71) Applicant (for all designated States except US): COPY-GUARD ENTERPRISES S.A. [LU/LU]; 672, rue de Neudorf, L-Luxembourg (LU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): WILNEN, Arie, Marinus [NL/GR]; 37A Psaron, GR-155 62 Holargos (GR).

(74) Agent: MOMMAERTS, J., H.; Exterpatent B.V., P.O. Box 90649, NL-2509 LP The Hague (NL).

(81) Designated States: AT (European patent), AU, BE (European patent), CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, KR, LU (European patent), NL (European patent), SE (European patent), SU, US.


Published

With international search report.

(54) Title: A METHOD AND AN APPARATUS FOR PREVENTING UNAUTHORIZED COPYING OF VIDEO SIGNALS ON TAPE

(57) Abstract

A method and an apparatus for modifying video signals in such a manner that, when recording said signals with a tape recording apparatus, the control of this apparatus is disturbed, which signals comprise image point signals grouped according to image lines and preceded, in each line, by a line synchronization pulse and a colour synchronization signal, the plurality of lines being combined to a frame preceded by a frame synchronization pulse, the image point signals being situated at one side, and the synchronization pulses at the other side of a zero level, in which additional pulses resembling line synchronization pulses having a deviating shape or situated in deviating points of a frame are added. In particular, in at least a part of the frames, in a number of last lines, the normal line synchronization pulses are removed in arbitrary locations, and, instead thereof, additional pulses with a deviating shape, and in particular a shorter duration, are introduced.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark				

A method and an apparatus for preventing unauthorized copying of video signals on tape.

In order to counteract unauthorized recording of video programmes legitimately recorded on tape or transmitted via television channels, it has already been proposed to modify the video signal series in such a manner that this is not perceptible in a reproducing apparatus, but that the control of an apparatus used for illegally recording these signals is sufficiently disturbed for making the recording unusable.

There is still a need for such an improvement of such methods that such disturbances cannot be removed by means of so-called time-base correctors.

The invention relates to a method for this purpose, according to which the video signals are of the kind mentioned in the preamble of claim 1, in which, according to the invention, additional pulses resembling line synchronization pulses with a deviating shape or in deviating points of a frame are added.

The additional pulses have the consequence that, in a recording apparatus, the amplification thereof is influenced in such a manner that the zero level in the subsequent part shifts towards the side of the synchronization pulses. In the case of claims 2 and 3 the recognizability of the subsequent frame synchronization pulses is reduced or removed, whereas, in the case of claims 4..6, the subsequent image point signals

will be suppressed or attenuated. In both cases the quality of the recorded image will be disturbed in such a manner that such a recording will become unsaleable. Since, in both cases, the location of the additional pulses in the frame can be
5 continually varied, it becomes virtually impossible to remove said disturbance.

The control circuits of a reproducing apparatus will not be influenced by these additional pulses, so that a tape with only modified signals remains as such suitable for normal
10 reproduction.

The invention will be elucidated below in more detail by reference to a drawing, showing in:

Figs. 1A..E video signal oscillograms for elucidating a first embodiment of the invention;

15 Fig. 2 a corresponding oscillogram, from which appears the disturbance occurring when unauthorizedly recording on tape video signals modified according to the invention; and

Figs. 3A..C oscillograms of an image line for elucidating a second embodiment of the invention.

20 In Fig. 1A the end of an image frame of a normal television image signal is shown. This comprises line synchronization pulses 2 situated below a zero line 1, image line signals 3 above this zero line, and a frame synchronization pulse signal 4 at the beginning of the next
25 frame and also situated below the line 1.

According to the invention, and as indicated at 5 in Fig. 1B, initially a number of image lines 3, e.g. 10..20 lines, with the corresponding line synchronization pulses 2 is removed. These lines lie, at any rate, already outside the
30 normal image frame, and can be done without therefore as such.

Subsequently, e.g. in the manner of Fig. 1C, in the interspace 5 thus obtained the original line synchronization pulses 2 are provided in specific points, and an interspace 5' will then remain.

35 In Fig. 1D is shown that the interspace 5' of Fig. 1C is filled with additional pulses 6, and Fig. 1E shows, at a

different time scale, that these pulses have a deviating shape, i.e. are shorter than the normal pulses 2.

These deviating pulses 6 have the consequence, that, when recording the signals in a tape recording apparatus, the control is disturbed. The oscillogram reproduced in Fig. 2 shows at 7 that, as a consequence of the deviating pulses, the zero level 1 is shifted towards the negative side, so that the synchronization circuit of the recording apparatus will not or badly recognize them as synchronization pulses, so that the frame synchronization is disturbed. The image quality becomes so bad that such tape recordings will be unsaleable.

This disturbing effect can be amplified by changing the location of the additional pulses 6, and then also more than one interspace 5' can be formed. This needs not to take place in each frame. In this manner a completely random disturbance can be obtained, so that the effect will be amplified still more, and suppression of the disturbance will be made virtually impossible.

A still further disturbance of video signals unauthorizedly recorded on tape can be obtained in the manner of Fig. 3. In Fig. 3A a normal line portion 3 of the signal of Fig. 1A is reproduced. This comprises a line synchronization pulse 2, a colour synchronization signal 8, and image signals 9, which, here, represent a grey wedge or the like.

According to the invention, as shown in Fig. 3B, after the colour synchronization signal 8 an additional pulse 6' is added, of which the length and location can vary. When recording such a signal with a tape recording apparatus, this additional pulse causes again the amplification control 1 to be affected, so that a portion of the subsequent image point signals 9 will be attenuated, which provides an additional deterioration of the image quality. Also this disturbance can be provided in arbitrary lines and/or frames.

An amplification of the effect can be obtained in the manner of Fig. 3C, in which the additional pulse 6' at its end is continued by an oppositely directed pulse 6".

Those above-mentioned disturbance manners can be used independently from one another, but provide, together, an optimal safety against unauthorizedly recording video signals on tape. The additional signals have no influence on the control circuits of an image reproducing apparatus having a synchronization which is simpler than that of the recording head of a tape recording apparatus. Circuits for executing the method according to the invention can be executed in different ways, and comprise mixing stages in which the additional pulses, which are generated synchronously with the pulses 2 of the video signal, are mixed in the envisaged points with the video signal according to a, in particular variable, program, or according to a random function.

C L A I M S

1. A method for modifying video signals in such a manner that, when recording said signals with a tape recording apparatus, the control of this apparatus is disturbed, which signals comprise image point signals grouped according to image lines and preceded, in each line, by a line synchronization pulse and a colour synchronization signal, the plurality of lines being combined to a frame preceded by a frame synchronization pulse, the image point signals being situated at one side, and the synchronization pulses at the other side of a zero level, characterized in that additional pulses resembling line synchronization pulses having a deviating shape or situated in deviating points of a frame are added.

2. The method of claim 1, characterized in that, at least in a part of the frames, in a number of last lines the normal line synchronization pulses are removed in arbitrary locations, and in that, instead thereof, additional pulses with a deviating shape, and in particular a shorter duration, are introduced.

3. The method of claim 2, characterized in that the points of introduction of additional pulses differ in the different frames.

4. The method of claim 3, characterized in that, in at least a part of the lines of a frame and between the colour synchronization signal and the image point signals, an additional pulse having the same sense as the line synchronization pulses is added.

5. The method of claim 4, characterized in that the location and/or the duration of the additional pulses are slowly varied.

6. The method of claim 4 or 5, characterized in that the additional pulses are continued with a pulse having the opposite sense beyond the zero level line.

7. An apparatus for executing the method of any one of claims 1..6, characterized by means for adding additional pulses to the image frames.

1/2






FIG. 1.




FIG. 2.






FIG. 3.

INTERNATIONAL SEARCH REPORT

International Application No. **PCT/EP 91/00738**

I. CLASSIFICATION F SUBJECT MATTER (If several classification symbols apply, indicate all) *

According to International Patent Classification (IPC) or to both National Classification and IPC

IPC⁵: H 04 N 5/91

II. FIELDS SEARCHED

Minimum Documentation Searched ?

Classification System	Classification Symbols
IPC ⁵	H 04 N

Documentation Searched other than Minimum Documentation
to the Extent that such Documents are Included in the Fields Searched *

III. DOCUMENTS CONSIDERED TO BE RELEVANT *

Category *	Citation of Document, ** with indication, where appropriate, of the relevant passages **	Relevant to Claim No. **
X	EP, A, 0364047 (COPYGUARD ENTERPRISES S.A.) 18 April 1990 see column 4, lines 4-21; column 5, lines 39-46	1,7
A	---	3,4
X	EP, A, 0199553 (J. RYAN) 29 October 1986 see column 5, line 5 - column 14, line 29	1,7
A	---	2,4,6
X	US, A, 4888649 (M. KAGOTA) 19 December 1989 see column 2, lines 30-68	1,7
X	GB, A, 2086641 (NIPPON VICTOR K.K.) 12 May 1982 see page 3, line 15 - page 5, line 99	1,7
A	---	2,4,6

* Special categories of cited documents: **

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Δ" document member of the same patent family

IV. CERTIFICATION

Date of the Actual Completion of the International Search

10th June 1991

Date of Mailing of this International Search Report

01.08.91

International Searching Authority

EUROPEAN PATENT OFFICE

Signature of Authorized Officer:

[Signature] Nurja TORIBIO

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)

Category *	Citation of Document, ¹⁾ with indication, where appropriate, of the relevant passages	Relevant to Claim No.
A	US, A, 4163253 (M. MORIO et al.) 31 July 1979 see column 4, line 3 - column 5, line 41 ---	6
A	US, A, 4571642 (R. HOFSTEIN) 18 February 1986 ---	
A	WO, A, 8605057 (A. WYNEN) 28 August 1986 ---	
A	EP, A, 0189548 (VPS VIDEO-PROGRAMM SERVICE GmbH) 6 August 1986 ---	
A	US, A, 4100575 (M. MORIO et al.) 11 July 1978 ---	
A	GB, A, 2055501 (I.V.S. LTD) 4 March 1981 ---	
A	GB, A, 1571386 (I.V.S LTD) 16 July 1980 ---	
A	Patent Abstracts of Japan, volume 9, no. 35 (E-296)(1758), 14 February 1985 & JP, A, 59178892 (YUUZOU UEHAGI) 11 October 1984 -----	

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

EP 9100738

SA 46631

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on 16/07/91. The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A- 0364047	18-04-90	NL-A- 8802494	01-05-90
		AU-A- 4495289	01-05-90
		CA-A- 2000423	11-04-90
		WO-A- 9004305	19-04-90
EP-A- 0199553	29-10-86	US-A- 4631603	23-12-86
		AU-B- 577011	08-09-88
		AU-A- 5607786	23-10-86
		CA-A- 1256558	27-06-89
		JP-A- 61288582	18-12-86
US-A- 4888649	19-12-89	JP-A- 63228888	22-09-88
GB-A- 2086641	12-05-82	JP-A- 57073587	08-05-82
		JP-A- 57075088	11-05-82
		DE-A, C 3142593	03-06-82
		US-A- 4488183	11-12-84
US-A- 4163253	31-07-79	JP-C- 1349150	28-11-86
		JP-A- 52114313	26-09-77
		JP-B- 61013667	15-04-86
		CA-A- 1095164	03-02-81
		DE-A- 2712844	06-10-77
		FR-A, B 2345877	21-10-77
		GB-A- 1571028	09-07-80
		NL-A- 7703169	27-09-77
US-A- 4571642	18-02-86	None	
WO-A- 8605057	28-08-86	NL-A- 8500515	16-09-86
		EP-A- 0214267	18-03-87
EP-A- 0189548	06-08-86	DE-A- 3443857	05-06-86
		JP-A- 61269472	28-11-86
US-A- 4100575	11-07-78	JP-C- 1327587	30-07-86
		JP-A- 52114312	26-09-77
		JP-B- 60052625	20-11-85
		AT-B- 355644	10-03-80

ANNEX THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

Page 2
EP 9100738
SA 46631

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on 16/07/91. The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A- 4100575		CA-A- 1088665	28-10-80
		DE-A,C 2712525	20-10-77
		FR-A,B 2345873	21-10-77
		GB-A- 1562763	19-03-80
		NL-A- 7703111	26-09-77
GB-A- 2055501	04-03-81	None	
GB-A- 1571386	16-07-80	None	